

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

Dodo Juice Shinecraft Hybrid Wax

Revision n Revision date 2021-03-30

SECTION 1: Identification of the substance/mixture and of the company/undertaking				
1.1. Product identifier				
Product name	Dodo Juice Shinecraft Hybrid Wax			

1.2. Relevant identified uses of the substance or mixture and uses advised against

CECTION 1. Identification of the substance/mixture and of the

Product Use [SU21] Consumer uses: Private households (= general public = consumers); [PC31] Polishes and wax blends; [AC1] Vehicles;

[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC31] Polishes and wax blends; [AC1] Vehicles;

1.3. Details of the supplier of the safety data sheet

Dodo Juice Limited Company Unit 10 **Address**

Golds Nurseries Business Park

Jenkins Drive Elsenham Bishops Stortford CM22 6JX

UK Web

www.dodojuice.com +44(0)1279 812687 factory@dodojuice.com Email address of the factory@dodojuice.com competent person

1.4. Emergency telephone number

Emergency telephone number +44(0)7891 096802 Company

Dodo Juice Ltd 0700-2300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC : EUH066; 1272/2008

2.2. Label elements

EUH066 - Repeated exposure may cause skin dryness or cracking. **Hazard Statement**

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Telephone

Email

Revision 0 Revision date 2021-03-30

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isopropanol	603-117-00-0	67-63-0	200-661-7		1 - 10%	Flam. Liq. 2: H225; Eye Irrit.
						2: H319; STOT SE 3: H336;
Hydrocarbons, C11-C13,			920-901-0		50 - 60%	EUH066; Asp. Tox. 1: H304;
isoalkanes, <2% aromatics						
Dimethyl siloxane, 3-		71750-80-6			1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2:
(2-aminoethyl)aminopropyldimethox						H319;
ysiloxy-terminated						
Low boiling naphtha <0.1% w/w		8052-41-3	232-489-3		0.5 - 1%	Flam. Liq. 3: H226; Asp. Tox.
benzene						1: H304; Skin Irrit. 2: H315;
						STOT RE 1: H372; Aquatic
						Chronic 3: H412;
Nonane		111-84-2	203-913-4		0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox.
						1: H304; Skin Irrit. 2: H315;
						STOT SE 3: H336; Aquatic
						Acute 1: H400; Aquatic
						Chronic 3: H412;
Trimethylbenzene (mixed isomers)		25551-13-7	247-099-9		0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox.
						1: H304; Skin Irrit. 2: H315;
						Eye Irrit. 2: H319; Acute Tox.
						4: H332; Aquatic Chronic 2:
Made	000 004 00 V	07.50.4	200 050 0		0 0 50/	H411;
Methanol	603-001-00-X	67-56-1	200-659-6		0 - 0.5%	Flam. Liq. 2: H225; Acute
						Tox. 3: H331; Acute Tox. 3:
						H311; Acute Tox. 3: H301; STOT SE 1: H370:
Ethydhoneono	601-023-00-4	100-41-4	202-849-4		0 0 50/	
Ethylbenzene	001-023-00-4	100-41-4	202-049-4		0 - 0.5%	Flam. Liq. 2: H225; Acute Tox. 4: H332:
						тох. 4. поэс;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical
	attention if irritation or symptoms persist.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical
	attention if irritation or symptoms persist.
Ingestion	DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.
4.2 Most important symptoms of	and offects, both courts and deleved

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to mucous membranes.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin. Repeated exposure may cause skin dryness or cracking.	
Ingestion	Ingestion may cause nausea and vomiting.	

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical. Water spray. Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Revision 0 Revision date 2021-03-30

	Nevision date 2021-03-06
6.1. Personal precautions, prote	ective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Surfaces contaminated with the product will become slippery.
6.2. Environmental precautions	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for co	ontainment and cleaning up
	Sweep up. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	3
	SECTION 8: Exposure controls/personal protection.
SECTION 7: Handling and s	torage
7.1. Precautions for safe handling	ng
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
7.3. Specific end use(s)	
	Avoid prolonged or repeated exposure. Wash hands after handling the product.
SECTION 8: Exposure contr	rols/personal protection
8.1. Control parameters	
8.1.1. Exposure Limit Values	

Revision 0 Revision date 2021-03-30

8.1.1. Exposure Limit Values

Ethylbenzene	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 441
	WEL 15 min limit ppm: 125	WEL 15 min limit mg/m3: 552
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Hydrocarbons, C11-C13,	WEL 8-hr limit ppm: 171	WEL 8-hr limit mg/m3: 1200
isoalkanes, <2% aromatics	NA (TO 1 1 1 1 1 1	NATE OF THE R. P.
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
Isopropanol	respirable dust: WEL 8-hr limit ppm: 400	respirable dust: WEL 8-hr limit mg/m3: 999
Isoproparior	''	· ·
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
Methanol	respirable dust:	respirable dust:
Methanoi	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 333
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
The other lives are a feet and	respirable dust:	respirable dust:
Trimethylbenzene (mixed	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 125
isomers)	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
	roopiiabio adoti	100pilabio adoli

DNEL: Derived no-effect level.

Exposure Pattern - Workers

Isopropanol	Long-term - inhalation - Systemic 500 mg/m³
	effects
	Long-term - dermal - Systemic 888 mg/kg
	effects

Exposure Pattern - General population

Isopropanol	Long-term - inhalation - Systemic 89 mg/m³	
	effects	
	Long-term - dermal - Systemic 319 mg/kg	Long-term - oral - Systemic effects 26 mg/kg
	effects	

8.2. Exposure controls

8.2.1. Appropriate engineering	Ensure adequate ventilation of the working area.
controls	
8.2.2. Individual protection	Wear suitable protective clothing.
measures	
Eye / face protection	Not normally required. Avoid contact with eyes.
Skin protection -	Chemical resistant gloves (PVC).
Handprotection	

SECTION 9: Physical and chemical properties

Revision 0
Revision date 2021-03-30

9.1. Information on basic physical and chemical properties

Appearance Paste Colour Beige Odour Aromatic Odour threshold No data available No data available Ηα Melting point 75 °C Freezing Point 75 °C Initial boiling point No data available Flash point No data available **Evaporation rate** No data available Flammability (solid, gas) No data available Vapour pressure No data available Vapour density No data available Relative density 0.834 (H2O = 1 @ 20 °C) **Fat Solubility** No data available Partition coefficient No data available Autoignition temperature No data available Viscosity 10000 x 10-6 m²/s @ 40 °C (ISO 3104/3105) **Explosive properties** No data available Oxidising properties No data available Solubility Insoluble in water

9.2. Other information

Conductivity
Surface tension
Gas group
Benzene Content
Lead content
VOC (Volatile organic compounds)
No data available
No data available
No data available
No data available
VOC (Volatile organic compounds)

SECTION 10: Stability and reactivity

1	n	1		P	ea	cti	iv,	itv	
- 1	· .		_	т			w	Hν	

No Significant Hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not applicable.

10.4. Conditions to avoid

Avoid sparks, flames, heat and sources of ignition.

10.5. Incompatible materials

Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and obnoxious fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity No data is available on this product.

Revision 0 Revision date 2021-03-30

		Revision date 2021-03-
11.1. Information on toxicologica	al effects	
Skin corrosion/irritation	May cause degreasing of the skin.	
Serious eye damage/irritation	May cause irritation to eyes.	
Respiratory or skin sensitisation	May cause irritation to skin in susceptible persons.	
Germ cell mutagenicity	No data is available on this product.	
Carcinogenicity	No data is available on this product.	
Reproductive toxicity	No data is available on this product.	
STOT-single exposure	No data is available on this product.	
STOT-repeated exposure	No data is available on this product.	
Aspiration hazard	No Significant Hazard.	
Repeated or prolonged exposure	May cause degreasing of the skin.	
11.1.4. Toxicological Information	1	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation Rat LC50/8 h: >5000mg/kg	Oral Rat LD50: >5000mg/kg
	Dermal Rabbit LD50: >5000mg/kg	
Isopropanol	Oral Rat LD50: 5840mg/kg	Dermal Rabbit LD50: 13900mg/kg
SECTION 12: Ecological info	ormation	
12.1. Toxicity		
Hydrocarbons, C11-C13,	Daphnia EC50/48h: 1000 mg/l	Algae IC50/72h: 1000 mg/l
isoalkanes, <2% aromatics	Dapinia 2000/4011. 1000 High	Algae 1000/1211. 1000 Hig/l
	Fish LC50/96h: 1000 mg/l	
Isopropanol	Fish LC50/96h: 10.0000 mg/l	Algae EC50/72h: >100mg/l
	Daphnia LC50/24h: 9714mg/l	Bacteria EC10/18h: >100mg/l
12.2. Persistence and degradab	ility	
<u> </u>	Expected to be biodegradable.	
12.3. Bioaccumulative potential		
12.3. Bioaccumulative potential		
	No data is available on this product.	
Partition coefficient	'	
	Dodo Juice Shinecraft Hybrid No data available	Hydrocarbons, C11-C13, No data available isoalkanes, <2% aromatics
	Wax	190ainai109, 72 /0 ai0i11au09
12.4. Mobility in soil		
	No data is available on this product.	
12.5. Results of PBT and vPvB	assessment	
	No data is available on this product.	
12.6. Other adverse effects	· ·	
	None.	
SECTION 13: Disposal cons	iderations	
13.1. Waste treatment methods		
	07 06 wastes from the MFSU of fats, grease, soaps, of	letergents, disinfectants and cosmetics.
General information	•	
	Dispose of in compliance with all local and national re	gulations
	1 2.55333 of its compliance with all local and hational re	ga.a.o.o.

Revision 0 Revision date 2021-03-30

Disposal methods	
	Can be incinerated if in compliance with local regulations.
SECTION 14: Transport	information
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping na	me
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class	s(es)
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazard	3
	The product is not classified as dangerous for carriage.
14.6. Special precautions fo	ruser
	The product is not classified as dangerous for carriage.
14.7. Transport in bulk acco	rding to Annex II of MARPOL 73/78 and the IBC Code
	The product is not classified as dangerous for carriage.
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulator	r information
15.1. Safety, health and env	ironmental regulations/legislation specific for the substance or mixture
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94

and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

lext of Hazard	Statements	ın
Section 3		

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Eye Irrit. 2: H319 - Causes serious eye irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

EUH066 - Repeated exposure may cause skin dryness or cracking.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Skin Irrit. 2: H315 - Causes skin irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

Aguatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H311 - Toxic in contact with skin.

Acute Tox. 3: H331 - Toxic if inhaled.

STOT SE 1: H370 - Causes damage to organs .

Revision 0 Revision date 2021-03-30

Other information	
	STOT SE 2: H371 - May cause damage to organs .
Maximum content of VOC	495 g/l.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.