

## SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/10

## **Dodo Juice Spirited Away**

Revision 1
Revision date 2020-11-26

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Address

Product name Dodo Juice Spirited Away

### 1.3. Details of the supplier of the safety data sheet

Company Dodo Juice Limited

Golds Nurseries Business Park

Jenkins Drive Elsenham Bishops Stortford CM22 6JX

UK

Unit 10

Web www.dodojuice.com
Telephone +44(0)1279 812687
Email factory@dodojuice.com
Email address of the competent person

### 1.4. Emergency telephone number

Emergency telephone number

Company

+44(0)7891 096802 Dodo Juice Ltd 0700-2300

### SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008

Flam. Liq. 1: H224; Eye Irrit. 2: H319; STOT SE 3: H336;

### 2.2. Label elements

## Hazard pictograms





# Signal Word

**Hazard Statement** 

Danger

Flam. Liq. 1: H224 - Extremely flammable liquid and vapour.

Eye Irrit. 2: H319 - Causes serious eye irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary Statement:

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting// equipment.

P242 - Use only non-sparking tools.

Revision 1
Revision date 2020-11-26

2.2. Label elements	
Precautionary Statement: Response	P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.  P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage  Precautionary Statement: Disposal	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to local and national regulations

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Revision 1
Revision date 2020-11-26

### 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isopropanol	603-117-00-0	67-63-0	200-661-7			Flam. Liq. 2: H225; Eye Irrit.
						2: H319; STOT SE 3: H336;
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics			920-901-0			EUH066; Asp. Tox. 1: H304;
(R)-p-Mentha-1,8-diene	601-029-00-7	5989-27-5	227-813-5		0 - 0.5%	Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;
Orange Oil Terpenes		8028-48-6	232-433-8			Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 1: H410;
monopropylene glycol		57-55-6	200-338-0		1 - 10%	
Ethylene glycol monobutyl ether	603-014-00-0	111-76-2	203-905-0		1 - 10%	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315;
Beta-pinene		127-91-3	204-872-5		0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;
L-Limonene	601-029-00-7	5989-54-8	227-815-6		0 - 0.5%	Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;
Eucalyptol		470-82-6	207-431-5		0 - 0.5%	Flam. Liq. 3: H226; Skin Sens. 1: H317;
1,7,7-Trimethylbicyclo[2.2.1]heptar 2-one	)-	76-22-2	200-945-0		0 - 0.5%	Flam. Sol. 2: H228; Acute  Tox. 4: H302; Acute Tox. 4:  H302+H332; Skin Irrit. 2:  H315; Eye Dam. 1: H318;  Acute Tox. 4: H332; STOT  SE 2: H371; Aquatic Chronic 2: H411;
Myrcene		123-35-3	204-622-5		0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Aquatic Acute 1: H400; Aquatic Chronic 2: H411;
alpha-Pinene		80-56-8	201-291-9		0 - 0.5%	Flam. Liq. 3: H226; Acute Tox. 4: H302; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 1: H410;

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## 4.2. Most important symptoms and effects, both acute and delayed

	<u> </u>
Inhalation	May cause drowsiness or dizziness. In severe cases, may cause loss of consciousness. Seek
	medical attention if irritation or symptoms persist.
Eye contact	Causes serious eye irritation. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Seek medical attention if irritation or symptoms persist.

## 4.3. Indication of any immediate medical attention and special treatment needed

4.5. Indication of any immediate medical attention and special treatment needed	
Inhalation	If you feel unwell, seek medical advice (show the label where possible).
Ingestion	If swallowed, seek medical advice immediately and show this container or label.

Revision 1
Revision date 2020-11-26

SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Carbon oxides.
5.2. Special hazards arising from	n the substance or mixture
	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear protective clothing.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.
6.2. Environmental precautions	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for co	ntainment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
6.4. Reference to other sections	
	SECTION 7: Handling and storage. SECTION 8: Exposure controls/personal protection.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handling	g
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
7.3. Specific end use(s)	
	Do not breathe gas/fumes/vapour/spray.
SECTION 8: Exposure contr	ols/personal protection
8.1. Control parameters	
8.1.1. Exposure Limit Values	

Revision 1
Revision date 2020-11-26

# 8.1.1. Exposure Limit Values

(R)-p-Mentha-1,8-diene	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm: 150	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Distillates (petroleum),	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 1200
hydrotreated light		NATE: 45 1 11 11 1 1 1
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
Ethylono alvoci monohytyl othor	respirable dust:	respirable dust:
Ethylene glycol monobutyl ether	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123
	WEL 15 min limit ppm: 50	<b>WEL 15 min limit mg/m3:</b> 101.2
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
Hydrogerhana C11 C12	respirable dust: WEL 8-hr limit ppm: 171	respirable dust: WEL 8-hr limit mg/m3: 1200
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	WEL 6-III IIIIII ppiii. 171	<b>VVEL 6-111 IIIIIL III.9/1113.</b> 1200
isoaikaries, 1270 aromaties	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Isopropanol	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
monopropylene glycol	WEL 8-hr limit ppm: 150	WEL 8-hr limit mg/m3: 474
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Sodium hydroxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2
	• •	•
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total - inhalable dust:
	inhalable dust: WEL 8-hr limit mg/m3 total  -	innalable dust: WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

DNEL: Derived no-effect level.		
Exposure Pattern - Workers		

Revision 1
Revision date 2020-11-26

## **Exposure Pattern - Workers**

Isopropanol	Long-term - inhalation - Systemic 500 mg/m³
	effects
	Long-term - dermal - Systemic 888 mg/kg
	effects
monopropylene glycol	Acute inhalation - Systemic 168 mg/m³
	effects

## **Exposure Pattern - General population**

Isopropanol	Long-term - inhalation - Systemic 89 mg/m³	
	effects	
	Long-term - dermal - Systemic 319 mg/kg	Long-term - oral - Systemic effects 26 mg/kg
	effects	
monopropylene glycol	Acute inhalation - Systemic 50 mg/m³	
	effects	

## 8.2. Exposure controls

8.2.1. Appropriate engineering	Ensure adequate ventilation of the working area.
controls	
8.2.2. Individual protection	Wear chemical protective clothing.
measures	
Eye / face protection	Approved safety goggles.
Skin protection -	Chemical resistant gloves (PVC).
Handprotection	
Respiratory protection	Wear suitable respiratory equipment when necessary.

# SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Blue
Odour	Perfumes/Alcoholic
Odour threshold	No data available
Melting point	Not applicable.
Freezing Point	<-20 °C
Initial boiling point	No data available
Flash point	18 °C (ASTM D-93)
Evaporation rate	No data available
Flammability (solid, gas)	Not applicable.
Vapour pressure	No data available
Vapour density	No data available
Relative density	0.8505 (H2O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	7 sec. 3 mm (ISO 2431)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Miscible in water

## 9.2. Other information

Revision 1
Revision date 2020-11-26

#### 9.2. Other information

Conductivity
No data available
No data available
No data available
Not applicable.

VOC (Volatile organic
compounds)

### SECTION 10: Stability and reactivity

### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Oxidising agents.

#### 10.4. Conditions to avoid

Heat, sparks and open flames.

#### 10.5. Incompatible materials

Amines. Strong bases. Strong oxidising agents.

#### 10.6. Hazardous decomposition products

Will not decompose if stored and used as recommended. Burning produces irritating, toxic and obnoxious fumes. Carbon dioxide (CO2). Carbon oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	Harmful if swallowed.	
	Repeated or prolonged exposure may cause dermatitis.	
Skin corrosion/irritation	May cause irritation to skin.	
Serious eye damage/irritation	Causes serious eye irritation.	
Respiratory or skin	No data is available on this product.	
sensitisation		
Germ cell mutagenicity	No data is available on this product.	
Carcinogenicity	No data is available on this product.	
Reproductive toxicity	No data is available on this product.	
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	No data is available on this product.	
Aspiration hazard	Potential for aspiration if swallowed.	
Repeated or prolonged	May cause degreasing of the skin. May cause dermatitis.	
exposure		

### 11.1.4. Toxicological Information

(R)-p-Mentha-1,8-diene	Oral Rat LD50: 4400mg/kg	Dermal Rabbit LD50: >5000mg/kg
Ethylene glycol monobutyl ether	Inhalation Rat LC50/4 h: 2.4mg/l	Oral Rat LD50: 470mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation Rat LC50/8 h: >5000mg/kg	Oral Rat LD50: >5000mg/kg
	Dermal Rabbit LD50: >5000mg/kg	
Isopropanol	Oral Rat LD50: 5840mg/kg	Dermal Rabbit LD50: 13900mg/kg
monopropylene glycol	Dermal Rat LD50: >2000 mg/kg	Oral Rat LD50: >20000 mg/kg

## SECTION 12: Ecological information

## 12.1. Toxicity

Revision 1
Revision date 2020-11-26

### 12.1. Toxicity

(R)-p-Mentha-1,8-diene	<b>Daphnia EC50/48h:</b> 69.6 mg/l	Fathead minnows LC50/96h: 0.702mg/l
Ethylene glycol monobutyl ether	<b>Daphnia EC50/48h:</b> 1000 mg/l	Fish LC50/96h: 1700.0000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	<b>Daphnia EC50/48h:</b> 1000 mg/l	Algae IC50/72h: 1000 mg/l
	Fish LC50/96h: 1000 mg/l	
Isopropanol	Fish LC50/96h: 10.0000 mg/l	Algae EC50/72h: >100mg/l
	<b>Daphnia LC50/24h:</b> 9714mg/l	Bacteria EC10/18h: >100mg/l
monopropylene glycol	<b>Daphnia LC50/48h:</b> >4850 mg/l	Guppy LC50/96h: >44000 mg/l
Orange Oil Terpenes	NOEC / EC10 for marine or >68.0000 mg/l freshwater organisms	

### 12.2. Persistence and degradability

Readily biodegradable.

### 12.3. Bioaccumulative potential

No data is available on this product.

### Partition coefficient

Dodo Juice Spirited Away No data available	Hydrocarbons, C11-C13, No data available
	isoalkanes, <2% aromatics

#### 12.5. Results of PBT and vPvB assessment

PBT no. vPvB no.

#### 12.6. Other adverse effects

Not determined.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

07 06 wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics.

### **General information**

Dispose of in compliance with all local and national regulations.

## Disposal methods

Do not empty into drains.

#### Disposal of packaging

Empty containers can be sent for disposal or recycling.

## **SECTION 14: Transport information**

#### Hazard pictograms



### 14.1. UN number

UN1219

## 14.2. UN proper shipping name

ISOPROPANOL

#### 14.3. Transport hazard class(es)

Revision 1
Revision date 2020-11-26

14.3. Transport hazard class(es	) )
ADR/RID	3
Subsidiary risk	1-
IMDG	3
Subsidiary risk	] -
IATA	3
Subsidiary risk	-
14.4. Packing group	
Packing group	П
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for us	er
	None.
14.7. Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code
	Not relevant.
ADR/RID	
Hazard ID	33
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-D
IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction	353
(Passenger)	
Maximum quantity	5 L
SECTION 15: Regulatory inf	formation
15.1. Safety, health and environ	mental regulations/legislation specific for the substance or mixture
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
15.2. Chemical safety assessment	ent
	No data available.
SECTION 16: Other informa	ition
Other information	
Revision	This document differs from the previous version in the following areas:.
	2 - 2.1.2. Classification - EC 1272/2008.
	9 - 9.1. Information on basic physical and chemical properties (Initial boiling point). 9 - 9.1. Information on basic physical and chemical properties (Melting point).
	9 - 9.1. Information on basic physical and chemical properties (Flammability (solid, gas)).
	0. 0.1 Information on basic physical and shaming properties (Autoinstition temporature)

9 - 9.1. Information on basic physical and chemical properties (Autoignition temperature).9 - 9.1. Information on basic physical and chemical properties (Explosive properties).

Revision 1
Revision date 2020-11-26

## Other information 9 - 9.1. Information on basic physical and chemical properties (Oxidising properties). 9 - 9.1. Information on basic physical and chemical properties (Vapour pressure). 9 - 9.1. Information on basic physical and chemical properties (Relative density). 9 - 9.1. Information on basic physical and chemical properties (Viscosity). 9 - 9.1. Information on basic physical and chemical properties (Vapour density). 9 - 9.1. Information on basic physical and chemical properties (Evaporation rate). 9 - 9.1. Information on basic physical and chemical properties (Freezing Point). 9 - 9.1. Information on basic physical and chemical properties (Fat Solubility). 9 - 9.1. Information on basic physical and chemical properties (Solubility). 9 - 9.1. Information on basic physical and chemical properties (Odour threshold). 9 - 9.2. Other information (Conductivity). 9 - 9.2. Other information (Partition coefficient). 9 - 9.2. Other information (Gas group). 9 - 9.2. Other information (Surface tension). 9 - 9.2. Other information (Product Subcategory). 9 - 9.2. Other information (Specific gravity). 11 - 11.1. Information on toxicological effects. 12 - 12.1. Toxicity. 16 - Maximum content of VOC. Text of Hazard Statements in Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Section 3 Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. EUH066 - Repeated exposure may cause skin dryness or cracking. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Flam. Lig. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H312 - Harmful in contact with skin. Acute Tox. 4: H332 - Harmful if inhaled. Flam. Sol. 2: H228 - Flammable solid. Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 2: H371 - May cause damage to organs . Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Maximum content of VOC 550 g/l. **Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.