

# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

# Dodo Juice Stripp-ex Panel Wipe

Revision 0
Revision date 2021-03-02

#### 1.1. Product identifier

Product name Dodo Juice Stripp-ex Panel Wipe

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use

[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC15] Non-metal-surface treatment products; [AC1] Vehicles;

\_\_\_\_

1.3. Details of the supplier of the safety data sheet

[SU21] Consumer uses: Private households (= general public = consumers); [PC15] Non-metal-surface treatment products; [AC1] Vehicles;

#### \_\_\_\_\_

## Company

**Dodo Juice Limited** 

Address

Unit 10

Golds Nurseries Business Park

Jenkins Drive Elsenham Bishops Stortford CM22 6JX

UK

Web
Telephone
Email

www.dodojuice.com +44(0)1279 812687

Email address of the competent person

factory@dodojuice.com factory@dodojuice.com

## 1.4. Emergency telephone number

#### Emergency telephone number

Company

+44(0)7891 096802 Dodo Juice Ltd

0700-2300

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008

: EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315;

#### 2.2. Label elements

### Hazard pictograms







#### Signal Word

**Hazard Statement** 

Danger

EUH066 - Repeated exposure may cause skin dryness or cracking.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Revision 0
Revision date 2021-03-02

#### 2.2. Label elements

	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.		
	Skin Irrit. 2: H315 - Causes skin irritation.		
Precautionary Statement:	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No		
Prevention	smoking.		
	P233 - Keep container tightly closed.		
	P240 - Ground/bond container and receiving equipment.		
	P241 - Use explosion-proof electrical/ventilating/lighting// equipment.		
	P242 - Use only non-sparking tools.		
	P243 - Take precautionary measures against static discharge.		
	P264 - Wash thoroughly after handling.		
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.		
Precautionary Statement:	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ .		
Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ soap.		
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse		
	skin with water/shower.		
	P321 - Specific treatment (see on this label).		
	P331 - Do NOT induce vomiting.		
	P332+P313 - If skin irritation occurs: Get medical advice/attention.		
	P370+P378 - In case of fire: Use to extinguish.		
Precautionary Statement:	P403+P235 - Store in a well-ventilated place. Keep cool.		
Storage	P405 - Store locked up.		
Precautionary Statement:	P501 - Dispose of contents/container to local and national regulations		
Disposal			

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Xylene	601-022-00-9	1330-20-7	215-535-7		40 - 50%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics			926-141-6		40 - 50%	EUH066; Asp. Tox. 1: H304;

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if irritation or symptoms persist.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Move the exposed person to fresh air. Rinse mouth thoroughly. Drink 1 to 2 glasses of water. Keep the affected person warm and at rest. DO NOT INDUCE VOMITING. Immediate medical attention is required.

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation. May cause irritation to respiratory system. Vapours may cause drowsiness and dizziness. Headache, nausea and vomiting.
Eye contact	Causes serious eye irritation.
Skin contact	Skin irritation and dermatitis.
Ingestion	May be fatal if swallowed and enters airways. Ingestion may cause nausea and vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Revision 0 Revision date 2021-03-02


4.3. Indication of any in	nmediate medical attention and special treatment needed
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Aspiration hazard.
SECTION 5: Firefigh	iting measures
5.1. Extinguishing med	ia
	Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
5.2. Special hazards ar	ising from the substance or mixture
	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back. Vapours are heavier than air.
5.3. Advice for firefighte	ers
	Self-contained breathing apparatus. Wear protective clothing.
SECTION 6: Accide	ntal release measures
6.1. Personal precaution	ns, protective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area. Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray.
6.2. Environmental pre	cautions
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and mate	rial for containment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
6.4. Reference to other	sections
	See section 8 for further information.
SECTION 7: Handlin	ng and storage
7.1. Precautions for saf	fe handling
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
7.2. Conditions for safe	storage, including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
7.3. Specific end use(s	
	Do not breathe gas/fumes/vapour/spray.
SECTION 8: Exposu	re controls/personal protection
8.1. Control parameters	5
8.1.1. Exposure Limit V	/alues

Revision 0
Revision date 2021-03-02

## 8.1.1. Exposure Limit Values

2,2'-Iminodiethanol	WEL 8-hr limit ppm: 3	WEL 8-hr limit mg/m3: 13
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total
	respirable dust:	respirable dust:
Hydrocarbons, C11-14,	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 1200
n-alkanes, isoalkanes, cyclic,		
<2% aromatics		
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total
	respirable dust:	respirable dust:
Xylene	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

#### 8.2. Exposure controls



## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Revision Revision date 2021-03-02

#### 9.1. Information on basic physical and chemical properties

Appearance Liquid

Colour Clear

Odour Aromatic

No data available Odour threshold

pН

Not applicable.

Melting point Not applicable.

Freezing Point No data available

Initial boiling point No data available

> Flash point 45 °C (ASTM D-93)

**Evaporation rate** No data available

Flammability (solid, gas) Not applicable.

Upper Explosive Limit

Lower Explosive Limit 0.9 %

> No data available Vapour pressure

Vapour density No data available

0.838 (H2O = 1 @ 20 °C) Relative density

**Fat Solubility** No data available

Partition coefficient No data available

Autoignition temperature 380 °C

> Viscosity 7 sec. 3 mm (ISO 2431)

No data available Oxidising properties

> Solubility Insoluble in water

#### 9.2. Other information

Conductivity No data available

Surface tension No data available

Gas group

No data available

Benzene Content No data available

Lead content

VOC (Volatile organic 838 g/l

compounds)

# SECTION 10: Stability and reactivity

#### 10.1. Reactivity

See section below for further information.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Combustible liquid. Keep away from incompatible materials.

#### 10.4. Conditions to avoid

Heat, sparks and open flames. Take precautionary measures against static discharges.

#### 10.5. Incompatible materials

Strong oxidising agents. halogenated hydrocarbons. Acids.

#### 10.6. Hazardous decomposition products

Will not decompose if stored and used as recommended. Burning produces irritating, toxic and obnoxious fumes

## SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects



Revision 0
Revision date 2021-03-02

11	1.1.	Information	on toxicol	logical	effects
----	------	-------------	------------	---------	---------

Acute toxicity	Oral Rat LD50 = >5000 mg/kg OECD 401.  Dermal Rabbit LD50 = >2000 mg/kg OECD 402.  Inhalation Rat LC50/4 h = >20 mg/l vapour OECD 403.
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritation	Irritating to eyes.
Respiratory or skin sensitisation	No sensitizaton effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	No carcinogenic effects reported.
Reproductive toxicity	No Significant Hazard.
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Repeated or prolonged exposure	May cause degreasing of the skin. May cause irritation to skin.

## 11.1.4. Toxicological Information

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics	Oral Rat LD50: 5000mg/kg	Dermal Rabbit LD50: 5000mg/kg
2,0 41.011.411.00	Inhalation Rat LC50/4 h: >5000mg/l	
Xylene	Oral Rat LD50: 4300 mg/kg	Dermal Rabbit LD50: 1100 mg/kg
	Inhalation Rat LC50/4 h: 28.1 mg/l	

# SECTION 12: Ecological information

## 12.1. Toxicity

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics	<b>Algae IC50/72h:</b> 20.0000 mg/l	Algae EC50/72h: >1000mg/l
	<b>Daphnia LC50/48h:</b> >1000 mg/l	Rainbow trout LC50/96h: >1000mg/l
	NOEC / EC10 for marine or 1.2200 mg/l freshwater organisms	
Xylene	Daphnia EC50/48h: 1.0000 mg/l	Algae IC50/72h: 2.2 mg/l
	Fish LC50/96h: 2.6000 mg/l	
	Toxic to aquatic organisms, may cause long-term a	adverse effects in the aquatic environment.
12.2 Persistence and degradal	pility	

#### 12.2. Persistence and degradability

No data is available on this product.

## 12.3. Bioaccumulative potential

No data is available on this product.

#### Partition coefficient

Dodo Juice Stripp-ex Panel Wipe No data available

## 12.4. Mobility in soil

Immiscible in water. Evaporates readily.

#### 12.5. Results of PBT and vPvB assessment

PBT no. vPvB no.

### 12.6. Other adverse effects

Revision 0
Revision date 2021-03-02

	Revision date 2021-03-02	
12.6. Other adverse effects		
	Toxic to aquatic organisms.	
SECTION 13: Disposal cons	siderations	
General information		
	Dispose of in compliance with all local and national regulations.	
Disposal methods		
	Dispose of this material and its container to hazardous or special waste collection point. Do not empty into drains.	
Disposal of packaging		
	Empty containers can be sent for disposal or recycling.	
SECTION 14: Transport info	prmation	
Hazard pictograms		
	3	
14.1. UN number		
	UN1307	
14.2. UN proper shipping name		
	XYLENES ((50% xylene))	
14.3. Transport hazard class(es		
ADR/RID	3	
Subsidiary risk	-	
IMDG	3	
Subsidiary risk IATA	3	
Subsidiary risk	- -	
14.4. Packing group	<u> </u>	
Packing group	III	
14.5. Environmental hazards	I '''	
Environmental hazards	No	
Marine pollutant	No	
ADR/RID	•	
Hazard ID	30	
Tunnel Category	(D/E)	
IMDG		
EmS Code	F-E S-D	
IATA		
Packing Instruction (Cargo)	366	
Maximum quantity	220 L	
Packing Instruction	355	
(Passenger) Maximum quantity	60 L	
modificati quality	1 **-	

Revision 0
Revision date 2021-03-02

# SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Regulations

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

#### 15.2. Chemical safety assessment

No data available.

#### SECTION 16: Other information

#### Other information

Text of Hazard Stat	ements in
Section 3	

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Skin Irrit. 2: H315 - Causes skin irritation.

EUH066 - Repeated exposure may cause skin dryness or cracking. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

#### Maximum content of VOC

838 g/l.

#### **Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.