

# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

## **Dodo Juice Taint it Black Trim Restorer**

Revision 0
Revision date 2021-03-25

	Revision date 2021-03-28
SECTION 1: Identification of	the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Dodo Juice Taint it Black Trim Restorer
1.2. Relevant identified uses of t	he substance or mixture and uses advised against
Product Use	[SU21] Consumer uses: Private households (= general public = consumers); [PC31] Polishes and wax blends; [AC1] Vehicles; [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC31] Polishes and wax blends; [AC1] Vehicles;
1.3. Details of the supplier of the	e safety data sheet
Company	Dodo Juice Limited
Address	Unit 10 Golds Nurseries Business Park Jenkins Drive Elsenham Bishops Stortford CM22 6JX UK
Web	www.dodojuice.com
Telephone	+44(0)1279 812687
Email	factory@dodojuice.com
Email address of the competent person	factory@dodojuice.com
1.4. Emergency telephone numb	per
Emergency telephone number	+44(0)7891 096802

Emergency telephone number	+44(0)7891 096802
Company	Dodo Juice Ltd
	0700-2300

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	: EUH066;	
2.2. Label elements		
Hazard Statement	EUH066 - Repeated exposure may cause skin dryness or cracking.	
2.3. Other hazards		
Other hazards	None.	

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Revision 0 Revision date 2021-03-25

#### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics			927-676-8		30 - 40%	EUH066; Asp. Tox. 1: H304;
Dimethyl siloxane, 3- (2-aminoethyl)aminopropyldimethox ysiloxy-terminated		71750-80-6			1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;
Low boiling naphtha <0.1% w/w benzene		8052-41-3	232-489-3		0.5 - 1%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT RE 1: H372; Aquatic Chronic 3: H412;
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics			920-901-0		1 - 10%	EUH066; Asp. Tox. 1: H304;
White Spirit		64742-82-1			1 - 10%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Aquatic Chronic 2: H411;
Isopropanol	603-117-00-0	67-63-0	200-661-7		0 - 0.5%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
Nonane		111-84-2	203-913-4		0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Acute 1: H400; Aquatic Chronic 3: H412;
Trimethylbenzene (mixed isomers)		25551-13-7	247-099-9		0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332; Aquatic Chronic 2: H411;
Ethyl butyrate		105-54-4	203-306-4		0 - 0.5%	Flam. Liq. 3: H226; Eye Irrit. 2: H319;
Methanol	603-001-00-X	67-56-1	200-659-6		0 - 0.5%	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370;
Ethylbenzene	601-023-00-4	100-41-4	202-849-4		0 - 0.5%	Flam. Liq. 2: H225; Acute Tox. 4: H332;

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to mucous membranes.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin. Repeated exposure may cause skin dryness or cracking.	
Ingestion	Ingestion may cause nausea and vomiting.	

### 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice (show the label where possible).

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical. Water spray. Do NOT use water jet.

#### 5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

Revision 0 Revision date 2021-03-25

	TOVISION data 2021 00 2
5.3. Advice for firefighters	
	Wear suitable respiratory equipment when necessary.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Ensure adequate ventilation of the working area. Surfaces contaminated with the product will become slippery.
6.2. Environmental precautions	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for co	ontainment and cleaning up
	Sweep up. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	
	SECTION 8: Exposure controls/personal protection.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handling	ng
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
7.3. Specific end use(s)	
	Avoid prolonged or repeated exposure. Wash hands after handling the product.
SECTION 8: Exposure contr	ols/personal protection
8.1. Control parameters	
-	
8.1.1. Exposure Limit Values	

Revision 0 Revision date 2021-03-25

#### 8.1.1. Exposure Limit Values

Fa u	N/ELOL # 400	WELDLE 1
Ethylbenzene	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 441
	WEL 15 min limit ppm: 125	<b>WEL 15 min limit mg/m3:</b> 552
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Hydrocarbons, C11-C13,	WEL 8-hr limit ppm: 171	WEL 8-hr limit mg/m3: 1200
isoalkanes, <2% aromatics		
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
I	respirable dust:	respirable dust:
Isopropanol	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	<b>WEL 15 min limit mg/m3:</b> 1250
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Methanol	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 333
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Trimethylbenzene (mixed	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 125
isomers)		NATE AT 1 11 1/2 / 2
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

DNEL: Derived no-effect level.

#### **Exposure Pattern - Workers**

Isopropanol	Long-term - inhalation - Systemic 500 mg/m³
	effects
	Long-term - dermal - Systemic 888 mg/kg
	effects

#### **Exposure Pattern - General population**

Isopropanol	Long-term - inhalation - Systemic 89 mg/m³	
	effects	
	Long-term - dermal - Systemic 319 mg/kg	Long-term - oral - Systemic effects 26 mg/kg
	effects	

#### 8.2. Exposure controls

8.2.1. Appropriate engineering	Ensure adequate ventilation of the working area.
controls	
8.2.2. Individual protection	Wear suitable protective clothing.
measures	
Eye / face protection	Not normally required. Avoid contact with eyes.
Skin protection -	Chemical resistant gloves (PVC).
Handprotection	

### SECTION 9: Physical and chemical properties

Revision 0 **Revision date** 2021-03-25

#### 9.1. Information on basic physical and chemical properties

Appearance Solid/Paste Colour Black Odour Perfumes Melting point 70 °C Freezing Point 70 °C Relative density 0.868 (H2O = 1 @ 20 °C) 1000 x 10-6 m<sup>2</sup>/s @ 40 °C (ISO 3104/3105) Viscosity Oxidising properties No data available Odour threshold No data available No data available **Fat Solubility** Partition coefficient No data available Autoignition temperature No data available Initial boiling point No data available Flash point No data available **Evaporation rate** No data available Flammability (solid, gas) No data available Vapour pressure No data available No data available Vapour density **Explosive properties** рΗ Not applicable. Solubility Insoluble in water

#### 9.2. Other information

VOC (Volatile organic	420 g/l
compounds)	
Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	Not applicable.

## CECTION 40. Stability and reactivity

SECTION 10: Stability and reactivity		
10.1. Reactivity		
	No Significant Hazard.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		
	Not applicable.	
10.4. Conditions to avoid		
	Avoid sparks, flames, heat and sources of ignition.	
10.5. Incompatible materials		
	Strong acids. Strong oxidising agents.	
10.6. Hazardous decomposition products		
	Burning produces irritating, toxic and obnoxious fumes.	
SECTION 11: Toxicological information		

11.1. Information on toxicological effects

May cause irritation to eyes and respiratory system.

Revision 0 Revision date 2021-03-25

44.4. Information on toxicologica	al officeto	
11.1. Information on toxicologica		
Acute toxicity	No data is available on this product.	
Skin corrosion/irritation	May cause degreasing of the skin.	
Serious eye damage/irritation	May cause irritation to eyes.	
Respiratory or skin sensitisation	May cause irritation to skin in susceptible persons.	
Germ cell mutagenicity	No data is available on this product.	
Carcinogenicity	No data is available on this product.	
Reproductive toxicity	No data is available on this product.	
STOT-single exposure	No data is available on this product.	
STOT-repeated exposure	No data is available on this product.	
Aspiration hazard	No Significant Hazard.	
Repeated or prolonged	May cause degreasing of the skin.	
exposure		
11.1.4. Toxicological Information	1	
Hydrocarbons, C11-C13,	Inhalation Rat LC50/8 h: >5000mg/kg	Oral Rat LD50: >5000mg/kg
isoalkanes, <2% aromatics		5. m. v. sa. 22. v. s. v. s.
	Dermal Rabbit LD50: >5000mg/kg	
Isopropanol	Oral Rat LD50: 5840mg/kg	Dermal Rabbit LD50: 13900mg/kg
SECTION 12: Ecological info	ormation	
12.1. Toxicity		
Hydrocarbons, C11-C13,	<b>Daphnia EC50/48h:</b> 1000 mg/l	Algae IC50/72h: 1000 mg/l
isoalkanes, <2% aromatics	Fish LC50/96h: 1000 mg/l	
Isopropanol	Fish LC50/96h: 10.0000 mg/l	Algae EC50/72h: >100mg/l
	<b>Daphnia LC50/24h:</b> 9714mg/l	Bacteria EC10/18h: >100mg/l
12.2. Persistence and degradab	ility	
	Expected to be biodegradable.	
12.3. Bioaccumulative potential		
· · · · · · · · · · · · · · · · · · ·		
	No data is available on this product.	
Partition coefficient	Two data is available of this product.	
Partition coefficient		
	Dodo Juice Taint it Black Trim No data available Restorer	Hydrocarbons, C11-C13, No data available isoalkanes, <2% aromatics
	Nestorer	isoairanes, 42% aromates
12.4. Mobility in soil		
	No data is available on this product.	
12.5. Results of PBT and vPvB	assessment	
	No data is available on this product.	
12.6. Other adverse effects		
	None.	
SECTION 13: Disposal cons	iderations	
13.1. Waste treatment methods		
	07 06 wastes from the MFSU of fats, grease, soaps,	detergents, disinfectants and cosmetics.
General information	1	<b>3</b> ,

Revision 0 Revision date 2021-03-25

General information		
	Dispose of in compliance with all local and national regulations.	
Disposal methods		
	Can be incinerated if in compliance with local regulations.	
SECTION 14: Transport information		
14.1. UN number		
	The product is not classified as dangerous for carriage.	
14.2. UN proper shipping nam	ne	
	The product is not classified as dangerous for carriage.	
14.3. Transport hazard class(es)		
	The product is not classified as dangerous for carriage.	
14.4. Packing group		
	The product is not classified as dangerous for carriage.	
14.5. Environmental hazards		
	The product is not classified as dangerous for carriage.	
14.6. Special precautions for	user	
	The product is not classified as dangerous for carriage.	
14.7. Transport in bulk accord	ling to Annex II of MARPOL 73/78 and the IBC Code	
	The product is not classified as dangerous for carriage.	
Further information		
	The product is not classified as dangerous for carriage.	
SECTION 15: Regulatory	information	
15.1. Safety, health and envir	onmental regulations/legislation specific for the substance or mixture	
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.	
15.2. Chemical safety assess	ment	

## **SECTION 16: Other information**

#### Other information

Outer information	
Text of Hazard Statements in	EUH066 - Repeated exposure may cause skin dryness or cracking.
Section 3	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
	Skin Irrit. 2: H315 - Causes skin irritation.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	Flam. Liq. 3: H226 - Flammable liquid and vapour.
	STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
	Aquatic Acute 1: H400 - Very toxic to aquatic life.
	Acute Tox. 4: H332 - Harmful if inhaled.
	Acute Tox. 3: H301 - Toxic if swallowed.

No data is available on this product.

Revision 0 Revision date 2021-03-25

Other information		
	Acute Tox. 3: H311 - Toxic in contact with skin.  Acute Tox. 3: H331 - Toxic if inhaled.	
	STOT SE 1: H370 - Causes damage to organs .	
	STOT SE 2: H371 - May cause damage to organs .	
Maximum content of VOC	420 g/l.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	